

Engine	Cummins QSF3.8
Gross Power	86 kW (117 hp)
Net Power	80.2 kW (109 hp)
Maximum Digging Depth	5,470 mm
Standard Bucket Capacity	0.6 m ³
Operating Weight	14,300 kg

915E

EXCAVATOR



TOUGH WORLD. TOUGH EQUIPMENT.

915E SPECIFICATIONS >>>

ENGINE

Emission Regulation	Tier 3 / Stage IIIA
Make	Cummins
Model	QSF3.8
Gross Power	86 kW (117 hp) @ 2,200 rpm
Net Power	80.2 kW (109 hp) @ 2,200 rpm
Peak Torque	470 N·m @ 1,500 rpm
Number of Cylinders	4
Displacement	3.76 L

TRACK DRIVE

Maximum Travel Speed	5.4 km/h
Drawbar Pull	124 kN

UNDERCARRIAGE

Shoe Width	600 mm
Number of Shoes per Side	46
Number of Bottom Rollers per Side	7
Number of Upper Rollers per Side	1

HYDRAULIC SYSTEM

Main Pumps Total Flow	240 L/min
Relief Pressure, main	34.3 MPa
Relief Pressure, boost	37 MPa

SWING SYSTEM

Swing Speed	12.94 rpm
-------------	-----------

REFERENCE ARM

Arm Length	2,500 mm
Arm Breakout Force, max, ISO	70 kN

WORKING RANGES

Maximum Dig Depth	5,470 mm
Reach at Ground Level	8,170 mm
Depth of 8' Level Bottom	5,250 mm
Maximum Dig Height	8,760 mm
Dump Height	6,310 mm
Maximum Dig Depth of Vertical Wall	5,250 mm

BUCKET PERFORMANCE

Standard Bucket Heaped Capacity (Referenced)	0.6 m³
Minimum Heaped Capacity of Bucket Options	0.36 m³
Maximum Heaped Capacity of Bucket Options	0.73 m³
Bucket Breakout Force, max, ISO	96.9 kN

SERVICE CAPACITIES

Fuel Tank	245 L
Engine Oil	14 L
Cooling System	21 L
Hydraulic Reservoir	160 L
Hydraulic System Total	240 L


Bucket: SAE 0.6 m³, 576 kg, Boom: 4,600 mm, Arm: 2,500 mm, Shoes: 600 mm, Counterweight: 2,300 kg

Lift Point Height												Max. Reach		
		2 m		3 m		4 m		5 m		6 m		Front	Side	mm
6.0 m	kg							※3,528	2,363			※3,585	2,210	5.2
5.0 m	kg							※3,464	2,368	3,119	1,750	3,119	1,750	6.0
4.0 m	kg					※3,946	3,289	※3,685	2,329	3,115	1,746	2,806	1,566	6.4
3.0 m	kg					※4,690	3,161	※4,076	2,263	3,080	1,714	2,530	1,400	6.8
2.0 m	kg					※5,543	3,011	4,006	2,183	3,032	1,671	2,397	1,316	7.0
1.0 m	kg			※8,840	※4,340	5,571	2,878	3,919	2,107	2,984	1,628	2,375	1,296	7.0
0 m	kg			※9,168	※4,215	5,462	2,787	3,853	2,048	2,944	1,591	2,457	1,334	6.8
-1.0 m	kg	※12,662	8,604	※9,030	※4,189	5,406	2,741	3,812	2,012	2,920	1,571	2,554	1,382	6.6
-2.0 m	kg	※11,640	8,661	※8,460	※4,198	5,394	2,731	3,800	2,003	2,921	1,572	2,921	1,572	6.0
-3.0 m	kg	※10,023	8,769	※7,450	※4,243	5,423	2,755	3,826	2,024			3,424	1,833	5.4

1. ※ Indicates the load is limited by hydraulic capacity rather than tipping capacity.

2. The above rated loads are in compliance with ISO 10567 hydraulic excavator lift capacity rating standard. They do not exceed 87% of hydraulic lifting capacity or 75% tipping load.

3. Ratings at bucket lift hook.



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment.

05/2016 Designed by LiuGong