

Engine	Cummins QSB7
Gross Power	169 kW(230 hp) @ 1,900 rpm
Net Power	156 kW(212 hp) @ 1,900 rpm
Maximum Digging Depth	7,300 mm
Standard Bucket Capacity	1.4 m ³
Operating Weight	31,800 kg

930E EXCAVATOR



TOUGH WORLD. TOUGH EQUIPMENT.

930E SPECIFICATIONS >>>

ENGINE

Emission Regulation	Tier 3 / Stage IIIA
Make	Cummins
Model	QSB7
Gross Power	169 kW(214.6 hp) @ 1,900 rpm
Net Power	156 kW(209.2 hp) @ 1,900 rpm
Peak Torque	895 N·m @ 1,300 rpm
Number of Cylinders	6
Displacement	6.7 L

TRACK DRIVE

Maximum Travel Speed	5.5 km/h
Drawbar Pull	255 kN

UNDERCARRIAGE

Shoe Width	600 mm
Number of Shoes per Side	48
Number of Upper Rollers per Side	2
Number of Bottom Rollers per Side	9

HYDRAULIC SYSTEM

Main Pumps Total Flow	532 L/min
Relief Pressure, main	34.3 MPa
Relief Pressure, boost	37.3 MPa

SWING SYSTEM

Swing Speed	10.3 rpm
-------------	----------

REFERENCE ARM

Arm Length	3,050 mm
Arm Breakout Force, max, ISO	149 kN

WORKING RANGES

Maximum Dig Depth	7,300 mm
Reach at Ground Level	10,453 mm
Depth of 8' Level Bottom	7,096 mm
Maximum Dig Height	10,240 mm
Dump Height	7,265 mm
Maximum Dig Depth of Vertical Wall	6,216 mm

BUCKET PERFORMANCE

Standard Bucket Heaped Capacity (Referenced)	1.4 m³
Minimum Heaped Capacity of Bucket Options	1.4 m³
Maximum Heaped Capacity of Bucket Options	1.6 m³
Bucket Breakout Force, max, ISO	203 kN

SERVICE CAPACITIES

Fuel Tank	520 L
Engine Oil	26 L
Cooling System	40 L
Hydraulic Reservoir	195 L
Hydraulic System Total	360 L

Bucket: SAE 1.4m ³ , 1,400 kg Boom: 6,200 mm Arm: 3,050 mm Shoes: 600 mm													
Lift Point Height													
		3 m		4 m		5 m		6 m		7 m		8 m	
7 m	kg									※4,670	※4,670		
6 m	kg									※5,900	※5,900		
5 m	kg							※6,450	※6,450	※6,260	※6,260	※5,080	※5,080
4 m	kg					※8,090	※8,090	※7,310	※7,310	※6,810	※6,810	※6,490	5,720
3 m	kg	※17,050	※17,050	※12,100	※12100	※9,710	※9,710	※8,330	※8,330	※7,460	7,000	※6,900	5,570
2 m	kg	※21,980	※21,980	※14,770	※14,770	※11,320	※11,320	※9,370	8,690	※8,150	6,770	7340	5,420
1 m	kg	※24,620	※24,620	※16,780	※16210	※12,690	11,200	※10,300	8,380	8,790	6,560	7,270	5,280
0	kg	※25,460	※25,460	※17,960	15,740	※13,660	10,850	11,020	8,130	8,860	6,390	7,150	5,170
-1 m	kg	※25,340	※25,340	※18,410	15,510	※14,190	10,640	11,230	7,970	8,740	6,270	7,070	5,170
-2 m	kg	※24,570	※24,570	※18,260	15,450	※14,260	10,550	11,140	7,890	8,680	6,220		
-3 m	kg	※23,180	※23,180	※17,540	15,510	※13,860	10,570	11,150	7,900	8,700	6,240		
-4 m	kg	※21,040	※21,040	※16,160	15,690	※12,860	10,680	※10,390	8,000				
-5 m	kg	※17,830	※17,830	※13,850	※13,850	※10,950	10,930						

1. ※ Indicates the load is limited by hydraulic capacity rather than tipping capacity.


2. The above rated loads are in compliance with ISO 10567 hydraulic excavator lift capacity rating standard. They do not exceed 87% of hydraulic lifting capacity or 75% tipping load.

3. Ratings at bucket lift hook.

1. ※ Indicates the load is limited by hydraulic capacity rather than tipping capacity.

2. The above rated loads are in compliance with ISO 10567 hydraulic excavator lift capacity rating standard. They do not exceed 87% of hydraulic lifting capacity or 75% tipping load.

3. Ratings at bucket lift hook.



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China

T: +86 772 3886124

E: overseas@liugong.com

www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment.

05/2014 Designed by Liugong